

Model: NB-S008GE

10/100 *8 Port+2 Giga Ethernet Uplink Port
250m PoE Switch With built-in Power Supply



Features

- 8*10/100Mbps PoE ports, 2*10/100/1000Mbps uplink port
- Support IEEE802.3af/at
- Support Max Transmission distance up to 250m with PoE Power
- Built-in power supply
- Maximum power of single PoE port: 30W
- Maximum PoE power:52V 120W
- Anti Thunder Design
- Power Circuit protection

Specification	Description
Network Port	8*10/100Mbps PoE RJ45 port
	2*10/100/1000 Mbps RJ45 port uplink
Transmission Distance	1 ~ 8 PoE Port : 100Mbps: 0~100 Meter ;
	1 ~ 8 PoE Port : 10Mbps: 0~250 Meter
Transmission Medium	Cat5/5e/6 standard network cable
Network Standard	IEEE802.3/802.3u, IEEE802.3x,IEEE802.ab
Performance	Switching Capacity:5.6 Gbps (no block)
	Packet Buffer Memory : 1Mbits
	Throughput : 1.488 Mbps, MAC Table: 1K
	Packet Forwarding rate : 10Mbps: 14880pps/port 100Mbps: 148800pps/port
Power Over Ethernet	PoE Standard: IEEE 802.3af/at
	PoE Power Supply: End-Span(1/2+;3/6-)
	PoE Power: af=15.4W,at=30W for each port
RJ 45 Port	Port Function: Power priority mechanism, fast and forward,
	MAC automatic learning and aging IEEE802.

	3X Full-duplex mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps;PoE Status Indicator; Power indicator; Extender
Environment	Operating Temperature : 0°~55°C
	Storage Temperature : -20°C~70°C
	Operating Humidity : 20%~ 95%, Non-condensing
Dimensions	Size (LxWxH) : 40mm*135mm*195mm
Certifications	CE/FCC/RoHS

Note: Product housing specifications are subject to change without prior notice. .