

Model: NT-IDN12

Spec: I3/P/2.8MM

2MP IR Dome Camera




Features

- Up to 1920X1080@30fps
- S+265/H.265/H.264 Codec
- Min. Illumination Color: 0.05 Lux,B/W: 0.01Lux,0 Lux with IR
- Smart IR, IR Range: 30m
- Operating Conditions -35°C~60°C(IR OFF) /-30°C~40°C(IR ON), 0~95% RHG
- PoE, IP66

Camera	
Image Sensor	1/2.9" CMOS
Signal System	PAL/NTSC
Min. Illumination	Color: 0.05Lux
	B/W: 0.01Lux
Shutter Time	1s to 1/100,000s
Lens	2.8mm
Lens Mount	M12
Day& Night	IR Cut Filter with Auto Switch
Wide Dynamic Range	100dB
Digital Noise Reduction	3D DNR
Compression Standard	
Video Compression	S+265/H.265/H.264
Video Bit Rate	32Kbps~8Mbps
Image	
Max. Image Resolution	1920x1080
Frame Rate	PAL:1080p@25fps, 960p@25fps, 720p@25fps, D1@25fps, VGA@25fps
	NTSC:1080p@30fps, 960p@30fps, 720p@30fps, D1@30fps, VGA@30fps
Mainstream	1080P(1920*1080)
Substream	4CIF (704x480)
Image Settings	Brightness, Saturation, Contrast, Flip Mode Adjustable by Client Software or Web Browser
HLC	Y
Smart Defog	Y
ROI	Y
Privacy Mask	Y
OSD	16x16, 32x32, 48x48,Size Letters Such as Week, Date, Time, Total 1 Regions

Network	
NTP	Y
Alarm Trigger	Motion Detection/IP Conflict/MAC Conflict
Protocols	TCP/UDP/HTTP /DHCP/DNS /NTP /RTSP
System Compatibility	ONVIF (Profile S)
Interface	
Audio Input	N/A
Audio Output	N/A
Communication Interface	1-ch RJ45 10M / 100M Ethernet Interface
On-board Storage	N/A
General	
Language	English, Simplified Chinese, Traditional Chinese, Spanish, Italian, Korean, Turkish, Russian, Thai, polish, French
Operating Conditions	-35°C~60°C, 0~95% RHG
Power Supply	DC 12 V ± 25%, POE
Power Consumption	MAX 7.5W (POE) , MAX 6W (DC12V)
IR Light	1
IR Distance	30m
Impact Protection	IP66
Dimensions	115mm(diameter)*97mm(height)
Weight	0.5KG



Note: Product specification and design are subject to change without any prior notice.